

Speedy Global Mount



Speedy Global Mount



Description

The Highfield Speedy Global Mount is a cost effective, easy to install locking device that secures the electric meter enclosure cover at both the side and/or the bottom of the enclosure. That means only one locking device is required for the simplicity of stocking and only one locking device is needed in the field. Therefore, installation time is kept to a minimum.

Incorporated into the design of the Speedy Global Mount, is a special four prong foot that bites into the inside wall of the enclosure minimizing movement after installation. No tools are required to install the Global Mount. Simply line up the mounting bracket where desired. Align the four prong foot using the swivel feature for optimum positioning and maximum strength. Press the four prong foot flush against the inside wall of the enclosure (side or bottom) and turn the mounting thumb screw clockwise until tight. Replace the enclosure cover, place the lock housing over the bracket stud and install a standard length barrel lock to complete the installation.

Benefits / Advantages

- Locks both Side & Bottom of Enclosure
- Case Hardened Carbon Steel for Added Strength
- Plated for Corrosion Resistance
- Four Prong Foot Swivel Feature for Optimum Positioning and Maximum Strength
- Uses Industry Standard Length Barrel Locks
- Can Pre-load Barrel Locks, Keys Not Required to Install
- Cost Effective / Short ROI Cycle



Part Numbers Description

93380318-G Speedy Global Mount w/Plastic Seal Ferrule. (Requires Std. Length Barrel Lock)